





SGS BEARINGS IMPORT LTD.



75 mm x 115 mm x 20 mm SKF 7015 ACD/P4AL angular contact ball bearings

Bearing No. 7015 ACD/P4AL

7015 ACD/P4AL Bearing 2D drawings and 3D CAD models

Size	115x75x20 mm
Bore Diameter	115 mm
Outer Diameter	75 mm
Width	20 mm
d	75 mm
D	115 mm
B	20 mm
d ₁	87.3 mm
d ₂	87.3 mm
D ₁	102.7 mm
b	1.8 mm
C ₁	10.9 mm
C ₂	3.9 mm
C ₃	3.4 mm
r _{1,2} - min.	1.1 mm
r _{3,4} - min.	0.6 mm
a	32.3 mm
d _a - min.	81 mm
d _b - min.	81 mm
D _a - max.	109 mm
D _b - max.	111 mm
r _a - max.	1 mm
r _b - max.	0.6 mm
d _n	90 mm



SGS BEARINGS IMPORT LTD.

Basic dynamic load rating - C	49.4 kN
Basic static load rating - C ₀	46.5 kN
Fatigue load limit - P _u	2 kN
Limiting speed for grease lubrication	10000 r/min
Limiting speed for oil lubrication	16000 mm/min
Ball - D _w	12.7 mm
Ball - z	20
G _{ref}	8.4 cm ³
Calculation factor - e	0.68
Calculation factor - Y ₂	0.87
Calculation factor - Y ₀	0.38
Calculation factor - X ₂	0.41
Calculation factor - Y ₁	0.92
Calculation factor - Y ₂	1.41
Calculation factor - Y ₀	0.76
Calculation factor - X ₂	0.67
Preload class A - G _A	310 N
Preload class B - G _B	620 N
Preload class C - G _C	1240 N
Preload class D - G _D	2480 N
Calculation factor - f	1.14
Calculation factor - f ₁	0.99
Calculation factor - f _{2A}	1
Calculation factor - f _{2B}	1.02
Calculation factor - f _{2C}	1.05
Calculation factor - f _{2D}	1.08
Calculation factor - f _{HC}	1



SGS BEARINGS IMPORT LTD.

Preload class A	200 N/micron
Preload class B	262 N/micron
Preload class C	347 N/micron
Preload class D	471 N/micron
d_1	87.3 mm
d_2	87.3 mm
D_1	102.7 mm
C_1	10.9 mm
C_2	3.9 mm
C_3	3.4 mm
$r_{1,2}$ min.	1.1 mm
$r_{3,4}$ min.	0.6 mm
d_a min.	81 mm
d_b min.	81 mm
D_a max.	109 mm
D_b max.	111 mm
r_a max.	1 mm
r_b max.	0.6 mm
d_n	90 mm
Basic dynamic load rating C	49.4 kN
Basic static load rating C_0	46.5 kN
Fatigue load limit P_u	1.96 kN
Attainable speed for grease lubrication	10000 r/min
Attainable speed for oil-air lubrication	16000 r/min
Ball diameter D_w	12.7 mm
Number of balls z	20
Reference grease quantity G_{ref}	8.4 cm ³
Preload class A G_A	310 N
Static axial stiffness, preload class A	200 N/ μ m



SGS BEARINGS IMPORT LTD.

Preload class B G_B	620 N
Static axial stiffness, preload class B	262 N/ μ m
Preload class C G_C	1240 N
Static axial stiffness, preload class C	347 N/ μ m
Preload class D G_D	2480 N
Static axial stiffness, preload class D	471 N/ μ m
Calculation factor f	1.14
Calculation factor f_1	0.99
Calculation factor f_{2A}	1
Calculation factor f_{2B}	1.02
Calculation factor f_{2C}	1.05
Calculation factor f_{2D}	1.08
Calculation factor f_{HC}	1
Calculation factor e	0.68
Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back-to-back, face-to-face) Y_1	0.92
Calculation factor (back-to-back, face-to-face) Y_2	1.41
Calculation factor (back-to-back, face-to-face) Y_0	0.76
Calculation factor (back-to-back, face-to-face) X_2	0.67
Mass bearing	0.63 kg